



Template for buttonholes, hems, pleats, scallops, etc.

This marking and measuring template is extremely versatile and simple. By means of the red slide, the required measure can be regulated very accurately.

There are two ways of using the template:




a) Using the edges if lines are required.




b) Using the small holes if points are required.

Examples:


1. **Marking of spaces for buttonholes, buttons, eyelets, pleats, etc.**
With the red slide, adjust the required space.
Transfer with points or lines onto the material.



2. Calculating the length of buttonholes




Flat buttons
Button and 2-3 mm



Ball shaped buttons (or thick fancy buttons)
Button and 5-8 mm

3. Marking of buttonholes


Transfer adjusted buttonhole length onto the garment.



Template for buttonholes, hems, pleats, etc.


4. Marking of hem depth

With the red slide adjust the required hem depth.
Put the red slide against the hem edge, mark the hem depth.



5. Marking of top-stitch lines


With the red slide regulate the required distance.
Put the red slide against the edge or seam. Mark the top-stitch line.




6. Drawing scallops

Drawing the curves:
Determine width and height of the curves
Draw the necessary subsidiary lines and mark central points
Regulate the slide, hold firm with pin or similar, draw the scallops
(use cardboard underlay).

Semicircular scallops



Flat scallops



Sequence of operations:
Preliminary drawing on paper
Definite drawing on soft cardboard (3 to 5 scallops)
Cut out the scallops (= cardboard template)
Transfer by means of the cardboard template onto the fabric
(using a light coloured crayon or a chalk crayon)

Bernina Dealers' notes regarding sewing instructions, home calls and possible guarantee work

Please observe the sewing position while sewing. The moving needle is a source of danger (danger of injury to fingers). The sewing machine should be disconnected from the power supply by pulling out the plug from the socket when changing the light bulb, the needle, presser foot, bobbin or needle plate, when stopping work without supervision and during servicing (cleaning).

Bernina Dealers' notes regarding sewing instructions, home calls and possible guarantee work

[illegible]

Subject to changes in design from those shown in text and illustrations.

[illegible]

BERNINA®

© Copyright by Fritz Gegauf Ltd., Steckborn/Switzerland

Address of my Bernina agency: